

## SNOW SWITCH MODEL APS-4C

### Automatic snow/ice melting system control panel

The APS-4C Snow Switch when used with one, or more, compatible sensors automatically controls snow/ice melting heaters for minimum energy costs. Applications include pavement, sidewalk, loading dock, roof, gutter and down spout snow /ice melting in commercial and industrial environments. The APS -4C is interchangeable with the earlier APS-4.


The adjustable hold -on timer continues heater operation for up to 10 hours after snow stops to ensure complete melting. The optional RCU-4 Remote Control Unit can be located where system operation can be conveniently observed. It duplicates many of the APS-4C front panel functions.

The APS-4 C provides advanced patented and patent pending ground fault equipment protection (GFEP) as required by the USA and Canadian National Electric Codes. The GFEP automatically tests itself every time the heater contactors operate and once every 24 hours. The trip current can be set at 60 or 120mA via an internal switch or retained at the 30mA default value. As an aid to troubleshooting heater ground faults, the APS -4C provides an output that can indicate the ground current on a service person 's portable DVM.

The calibrated 40°F to 90°F (4°C to 32 °C) high limit thermostat prevents excessive temperatures when using constant wattage and MI heaters. It also permits safe testing at outdoor temperatures too high for continuous heater operation. The temperature sensor is included. The APS -4 C provides a complete interface for use in environments supervised by an energy management computer (EMC). This feature can also be used for general purpose remote control and annunciation.

All sensor and communications wiring are NEC Class 2. This simplifies installation while enhancing fire and shock safety. The APS-4C can interface up to six sensors from the CIT-1 product family. Using more sensors provides superior performance by better matching the controller to site performance requirements.

The APS-4 C is an exceptionally capable deicing controller. For complete information describing its application, installation and features, please contact Customer Service or check on the web at [www.networketi.com](http://www.networketi.com).



### Features and Benefits

- Automatic snow/ice melting control
- Satellite contactor interface for larger systems
- Energy management computer (EMC) interface
- Accommodates MI, constant wattage and self-limiting heaters
- Multiple sensor capability
- Advanced patented and patent pending ground fault protection
- Heater hold-on and test capabilities
- C-UL-US
- Simple to install and operate
- Low system costs
- Minimum energy costs

## Specifications

### General

Area of use:	Non-hazardous locations
Approvals:	C-UL-US Type 873 Temperature Regulating Equipment Also evaluated by Underwriters Laboratories Inc® in accordance with UL 1053 Ground-Fault Sensing and Relaying Equipment

### Enclosure

Protection:	NEMA 3R
Cover attachment:	Hinged polycarbonate cover, lockable
Entries:	One 1-1/16" entry (top) for NEC Class 2 connections Two 1-1/16" entries (bottom) for supply and load power, except 277V single phase Two 1-1/16" entries (bottom) for supply and load power, 277 V single phase only
Material:	Polycarbonate
Mounting:	Wall mount
Dimensions:	9 .125" (L) x 11.500" (W) x 6.56 2" (H) 232mm (L) x 292mm (W) x 167mm (H)

### Control

Supply voltage:	208-240 VAC, 35 VA, three phase 50/60 Hz 277 VAC, 45 VA, single phase 50/60 Hz 277/480 VAC, 45 VA, three phase 50/60 Hz 600 VAC, 50 VA, three phase 50/60 Hz
Load:	208-240 VAC, 50 amp max. resistive 277 VAC, 40 amp max. resistive 277/480 VAC, 50 amp max. resistive 600 VAC, 50 amp max. resistive
Contact type:	3 Form A
Weight:	3 Pounds

### Control (continued)

Maximum ratings:	Voltage: 600 V Current: 50 A except 277 V single phase, 40 A for 277 V single phase
Heater hold-on timer:	0 to 10 hours; actuated by snow stopping or toggle switch
System test:	Switch toggles heater contact on and off. If temperature exceeds optional high limit thermistor (45°F), heater shuts off to reduce costs and prevent damage.

### Front panel interface

Status indicator:	- SUPPLY (green): Power on - HEAT (yellow): Heating cycle in progress - SNOW (yellow): Sensor(s) detect snow - GFEP (red): Ground Fault condition - GFEP (red, flashing): Failed - GFEP (red, rapid flashing): GFEP test in progress
-------------------	---

### Communication Bus

Number of cascaded units:	Unlimited
Contact delay:	5 second
Bus-wire type:	3-wire jacketed cable
Circuit type:	NEC Class 2
Lead length:	Up to 500' (152m) using 18 AWG 3-wire jacketed cable Up to 2,000' (609m) using 12 AWG 3-wire jacketed cable

### Ground Fault Equipment Protection (GFEP)

Set point:	30 mA (default); 60 mA and 120 mA selectable by DIP switch
Automatic self-test:	Mode A: Verifies GFEP function before contactors operate Mode B: Verifies GFEP and heaters every 24 hours

### Environmental


Operating temperature:	-40°F to 160°F (-40°C to 71°C)
Storage temperature:	-50°F to 180°F (-45°C to 82°C)

## Ordering Information

Order Number	Description
<b>22472</b>	APS-4C, 208- 240 VAC 50/ 60 Hz Three Phase
<b>22473</b>	APS -4C, 2 77 VAC 50/60 Hz Single Phase
<b>22475</b>	APS-4C , 277/480 VAC 50/ 60 Hz Three Phase
<b>22476</b>	APS-4 C, 600 VAC 50/60 Hz Three Phase

Accessories	Description
<b>21358</b>	RCU-4 Remote Control (Optional)
<b>19272</b>	High Temperature Sensor w/ 20' (6m) lead
<b>22690</b>	PTS-100 Embedded Temperature Sensor (Optional)

## Dimensional Drawings



### Limited Warranty

ETI's two year limited warranty covering defects in workmanship and materials applies. Contact Customer Service for complete warranty information.

### Disclaimer

ETI makes no representations or warranties, either expressed or implied, with respect to the contents of this publication or the products that it describes, and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose. ETI reserves the right to revise this publication, and to make changes and improvements to the products described in this publication, without the obligation of ETI to notify any person or organization of such revisions, changes or improvements.

The ETI logo, Snow Switch, We Manage Heat, CIT, GIT, and SIT are registered trademarks of ETI. PD Pro and RCU are trademarks of ETI. Copyright © 2013 ETI. All rights reserved.

### Contacting Customer Service

For assistance, contact Customer Service. Office hours are from 8:00 AM until 5:00 PM ET.

**Email:** [info@networketi.com](mailto:info@networketi.com)

**Web:** [networketi.com](http://networketi.com)

**Mail:** ETI  
 1850 North Sheridan Street  
 South Bend, IN 46628