

# ORF-P

## 120V Preassembled Series Resistance Heating Cable for Pipes

### Features

#### Nominal voltage

- 120V.

#### Linear density

- 7 Watts per foot.

#### Cold lead length

- 30 in. (0.76 m).

#### Outer jacket

- PVC.

#### Bus wire

- Nickel plated copper.

#### Minimum bend radius

- 5/16 in. (8 mm).

#### Included hardware

- Built-in bi-metal thermostat energizes the cable when temperature falls below 4 °C (40 °F).
- Grounded 3-pronged plug with indicator light to show when the cable is on.

#### Installation

- Never cut or shorten the heating cable.
- Installation under the insulation of the pipe.
- For indoor and outdoor applications.
- Minimum installation temperature: 0 °C (34 °F).

#### Warranty

- 1-year basic warranty on the heating cable.

#### Application

- Metallic and non-metallic pipes.
- Helps to prevent damage caused by frozen pipes.





## Models

Product # <sup>1</sup>	Length		Watts
	ft.	m	
ORF-P003	3	0.9	21
ORF-P006	6	1.8	42
ORF-P009	9	2.7	63
ORF-P012	12	3.7	84
ORF-P015	15	4.6	105
ORF-P018	18	5.5	126
ORF-P024	24	7.3	168
ORF-P030	30	9.0	210
ORF-P040	40	12.2	280
ORF-P060	60	18.3	420
ORF-P080	80	24.4	560

<sup>1</sup> Must be plugged into a 120V outlet fitted with ground fault protection device (GFCI).